



2K, ANGLE UTILITY

60" WIDE DECK



Model #'s	Liberty Utility
LU2K60X8A	Liberty Utility 2,000 lb GVWR 5' X 8'
LU2K60X10A	Liberty Utility 2,000 lb GVWR 5' X 10'
Tire Options	Description
SA175/80D13S-0	175/80D13 LRC BIAS, Silver Spoke Wheel
SA175/80R13SS-U	175/80R13 LRC RADIAL, Silver Spoke Wheel
Coupler Options	Description
CO3.5K2ST	2" STRAIGHT COUPLER
Jack Options	Description
JOSWING	800 LB SWING JACK W/ CASTER WHEEL
Fender Options	Description
FO9X29.75WB	9" X 29.75" ROLLED FENDERS
Lighting Options	Description
LOLUSEALDBEAM	SEALED BEAM LIGHTS
LOLULED	LED SEALED BEAM LIGHTS
Tail Options	Description
TO9G60X48ANGL	48" ANGLE GATE, 9 GA EXPANDED
TO9G60X48TUBE	48" TUBE GATE, 9 GA EXPANDED
TO9G60X48ANGL LDR	48" ANGLE LADDER GATE, 9 GA EXPANDED
TO9G60X48TUBE LDR	48" TUBE LADDER GATE, 9 GA EXPANDED
TOSPRINGSUT	SET OF UTILITY GATE SPRINGS
Other Options	Description
OO2X2TR60X(L)	2" X 2" ANGLE TOP RAIL
OO2.5X1.5TTR60X(L)	2 1/2" X 1 1/2" TUBE TOP RAIL
OOXFLR60X(L)	9 GA EXPANDED METAL FLOOR, PRICED PER FT
OOWDFLR60X(L)	2" TREATED PINE FLOOR, PRICED PER FT
OOSPMNT	SPARE TIRE MOUNT ONLY
OO175DSPR	BIAS SPARE TIRE AND WHEEL MOUNTED ON TRAILER
OO175RSPR	RADIAL SPARE TIRE AND WHEEL MOUNTED ON TRAILER
Standard Features	2,000 Lbs. GVWR
BED WIDTH	5'
LENGTHS	8', 10'
AXLE(S)	2,000 lb Straight Ultra Lube
TIRES & WHEELS	175/D13 LRC Mod Wheel
ELEC BRAKES	Idler Axle
SUSPENSION	Eye-To-Eye Springs
COUPLER	2" Straight
JACK	N/A
CHASSIS	2" X 2" X 1/8" Angle
TONGUE	3" X 2" X 1/8" Tube
CROSS MEMBERS	2" X 2" X 1/8" Angle
UPRIGHTS	2" X 2" X 1/8" Angle
FENDERS	Roll Formed
ELECTRICAL	Industrial Grade Sealed Wiring Harness
FINISH PREP	Degreased, Acid Washed, Sealer Rinsed
FINISH	Powder Coated